10K CAST IRON, GATE VALVE FLANGED ENDS

KITZ Fig: 10FCHI

Sizes: 11/2-12inch(40-300mm)

BOLTED BONNET, INSIDE SCREW, NON RISING STEM, FLAT FACE FLANGED

ENDS. Standards

. End to End: BS 3464

End Connection: JIS B2239 10KWall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

SIZE(inc	ch/mm)	L	L1	Н	D1	Kg
11/2	40	140.0	0.0	210.0	140.0	0.00
2	50	146.0	0.0	250.0	140.0	0.00
21/2	65	159.0	0.0	285.0	160.0	0.00
3	80	165.0	0.0	350.0	160.0	0.00
4	100	171.0	0.0	400.0	180.0	0.00
5	125	190.0	0.0	460.0	225.0	0.00
6	150	210.0	0.0	515.0	225.0	0.00
8	200	241.0	0.0	635.0	300.0	0.00
10	250	273.0	0.0	760.0	350.0	0.00
12	300	305.0	0.0	870.0	350.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	CAST IRON	FC300	
BONNET	CAST IRON	FC300	
STEM	FORGED BRASS	C3771	
DISC	CAST BRONZE	CAC	

Specifications


10K CAST IRON, GATE VALVE FLANGED ENDS, BOLTED BONNET, INSIDE SCREW, NON RISING STEM, FLAT FACE FLANGED ENDS.

End to End : BS 3464, End Connection : JIS B2239 10K, Wall

Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 11/2-12inch(40-300mm), BODYMATERIAL: CAST IRON, BONNETMATERIAL: CAST IRON, STEMMATERIAL: FORGED BRASS, DISCMATERIAL: CAST BRONZE, KITZ Fig

: 10FCHI





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



