10K CAST IRON SWING CHECK VALVE FLANGED ENDS

KITZ Fig: 10FC0

Sizes: 11/2-12inch(40-300mm)

BOLTED COVER, FLAT FACE FLANGED ENDS.

Standards

. End to End: JIS B2031

End Connection: JIS B2239 10KWall Thickness: JIS B2031

Test Standard
. KITZ STANDARD

Approvals

JIS Product Certification, Lead Free 40-300 mm (11/2-12 inch) approved

Dimensions

211110110110110						
SIZE(inch/mm)		L	L1	Н	D1	Kg
11/2	40	190.0	0.0	108.0	0.0	0.00
2	50	200.0	0.0	113.0	0.0	0.00
21/2	65	220.0	0.0	123.0	0.0	0.00
3	80	240.0	0.0	145.0	0.0	0.00
4	100	290.0	0.0	165.0	0.0	0.00
5	125	360.0	0.0	207.0	0.0	0.00
6	150	410.0	0.0	225.0	0.0	0.00
8	200	500.0	0.0	271.0	0.0	0.00
10	250	620.0	0.0	319.0	0.0	0.00
12	300	700.0	0.0	356.0	0.0	0.00



NAME OF PART	MATERIAL	SPECIFICATION
BODY	CAST IRON	FC200
COVER	CAST IRON	FC200
DISC	CAST IRON	FC200

Specifications

10K CAST IRON SWING CHECK VALVE FLANGED ENDS, BOLTED COVER, FLAT FACE FLANGED ENDS.


End to End : JIS B2031, End Connection : JIS B2239 10K, Wall Tchickness : JIS B2031, Test Standard : KITZ STANDARD, Sizes : 11/2-12inch(40-300mm), Approvals : JIS Product Certification, Lead

Free 40-300 mm (11/2-12 inch), BODYMATERIAL :CAST

IRON, COVERMATERIAL : CAST IRON, DISCMATERIAL : CAST IRON, KITZ Fig :

10FC0





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



