10K DUCTILE IRON Y TYPE STRAINER FLANGED ENDS

KITZ Fig: 10FDYBF

Sizes: 1/2-12inch(15-300mm)

SCREWED CAP, FLAT FACE FLANGED ENDS.

Standards

End to End: KITZ STANDARD
 End Connection: JIS B2239 10K
 Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

D I III CITO I OTTO						
SIZE(inch/mm)		L	L1	Н	D1	Kg
1/2	15	125.0	0.0	57.0	0.0	0.00
3/4	20	140.0	0.0	62.0	0.0	0.00
1	25	150.0	0.0	77.0	0.0	0.00
11/4	32	170.0	0.0	90.0	0.0	0.00
11/2	40	190.0	0.0	100.0	0.0	0.00
2	50	230.0	0.0	138.0	0.0	0.00
21/2	65	305.0	0.0	207.0	0.0	0.00
3	80	360.0	0.0	237.0	0.0	0.00
4	100	415.0	0.0	279.0	0.0	0.00
5	125	465.0	0.0	321.0	0.0	0.00
6	150	515.0	0.0	367.0	0.0	0.00
8	200	580.0	0.0	461.0	0.0	0.00
10	250	680.0	0.0	534.0	0.0	0.00
12	300	800.0	0.0	623.0	0.0	0.00



NAME OF PART	MATERIAL	SPECIFICATION
BODY	DUCTILE IRON	FCD-S
COVER	DUCTILE IRON	FCD-S


Specifications

10K DUCTILE IRON Y TYPE STRAINER FLANGED ENDS, SCREWED CAP, FLAT FACE FLANGED ENDS.

End to End: KITZ STANDARD, End Connection: JIS B2239 10K, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/2-12inch(15-300mm), BODYMATERIAL: DUCTILE IRON, COVERMATERIAL

:DUCTILE IRON, KITZ Fig : 10FDYBF





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



